






- NOTES:
1. INSTALLATION SHALL COMPLY WITH ALL APPLICABLE NATIONAL, STATE AND LOCAL CODES.
 2. PLEASE REFER TO PRODUCT DOCUMENTATION FOR FURTHER INFORMATION.
 3. UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE IN MILLIMETERS (INCHES).
 4. MOUNTING BUTTON IS AN ALTERNATIVE MOUNTING METHOD TO THE TOOLLESS MOUNT FOR 3RD PARTY ENCLOSURE. BUTTON IS PROVIDED WITH THE UNIT. DETAILED INSTALLATION INSTRUCTIONS CAN BE FOUND IN THE PROVIDED MANUAL.
 5. BRACKET KITS TO MOUNT TO SPECIFIC 3RD PARTY ENCLOSURES ARE AVAILABLE AS OPTIONS.
 6. RARITAN STANDARD LENGTH OF THE CORD IS 3000MM+/-70MM
 7. DIMENSION TOLERANCE: LENGTH +/-3MM, WIDTH +/-1MM, DEPTH +/-0.5MM



Raritan® A brand of  legrand®			 PROJECTION THIRD ANGLE	DO NOT SCALE DRAWING	SPECIFICATION	
		SHEET 1 OF 1		iPDU Zero U 200-240V, 32A Plug Type: IEC60309 32A Outlet Type: Locking HDOT C13 (18), Locking CX (18)		
Drawing Maker:	Eva Lin	Jan. 23, 2026	THIS DRAWING AND SPECIFICATIONS HEREIN ARE THE PROPERTY OF RARITAN, Inc. AND SHALL NOT BE COPIED, REPRODUCED OR USED, IN WHOLE OR IN PART, AS THE BASIS FOR THE MANUFACTURE OR SALE OF ITEMS WITHOUT WRITTEN PERMISSION FROM RARITAN, Inc. THIS DRAWING IS BASED UPON LATEST AVAILABLE INFORMATION AND IS SUBJECT TO CHANGE WITHOUT NOTICE.			
Design Engineer:	Eva Lin	Jan. 23, 2026				
Approver:	Tom Hsueh	Jan. 23, 2026				
			DWG NO.	MPX4-5057-E7 & MPX4-5057-E7M27		
			MODEL NO.	PX4-5057-E7 & PX4-4057-E7 PX4-5057-E7M27 & PX4-5057-E7M27	REV. 0F	