

NOVUS TSS-LiftTEC arm I Dual

The high-grade NOVUS TSS-LiftTEC®-Arm I Dual of diecast aluminium is a double monitor supporting arm for the high-quality attachment of two monitors one upon the other or side by side for mounting at every Novus TSS column (excepting TSS column with system clamp and base). A gas pressure spring allows the monitors height to be infinitely adjusted with just two fingers. The arm can be pivoted 180° in the working area, has a reach up to 447 mm and two ball-joints for almost unlimited freedom of movement for every monitor. Setting the user's ideal position is consequently child's play and a change of posture possible at any time. The quick-release mechanism with 1-lever operation allows each of the two monitors weighing 3-7 kg to be attached without undue effort. It is equipped with the standard, widely used flat-screen mount 75 x 75 and 100 x 100 for the mounting of all normal flat-screens. The monitor cables are guided through a cable clamp .



The LiftTEC® arm with gas spring technology can be infinitely adjusted to any height with incredible ease.



The adapter plate permits the straightforward attachment of all monitors with the standard 75 or 100 mount.



The product can be turned to either side and has the mentioned reach in mm.



The weight indicates the maximum load-bearing capacity of the supporting element or the maximum weight of an attachable monitor in kilograms.



When used conventional.



This machine bears the GS approval of product safety.



Available in silver/ anthracite



Art.No. :
980+1279+000
Bar code :
4009729046463

NOVUS TSS-LiftTEC arm I Dual



Cables are routed through the base of the LiftTEC arm.



The monitor is attached and released with effortless ease thanks to the new, simple Quick Release system with single-lever operation.



Monitor is easy to attach using QuickRelease with single-lever operation. Ball-joint for selecting the optimum viewing angle as well as for utilising the monitor pivoting function.



Cable clips for perfect cable management along and in the support arm.



Adjustable gas springs allow the LiftTEC® arm to be adjusted to the weight of the monitor.



The easy-action rotating joints can be adjusted to any position.



The LiftTEC® arm with convenient gas spring technology can be infinitely adjusted to any height with incredible ease.