

SMS PROJECTOR SHORT THROW WALL MANUAL



Stable, and perfectly easy to adjust its height.

Pull the handle up or down, and feel how the low-friction design ensures that the interactive board moves nearly by itself. Add to this the greater stability of the construction and handle, and you have a bracket that is suitable for both conferences and schools. Children can reach easily high up on the board, and

the adjustability means that no-one has to stretch unnecessarily. The bracket's low weight, and the fact that much of it has been pre-assembled, mean that one person can complete the assembly in under an hour. The universal fitting can be used with most currently available boards.

INFO

- Finish: Aluminium/white
- Tilt SMS projector slide: $\pm 15^\circ$
- Lengths: 605 mm (main column).
450/680/1200/1450 mm (projector rail).
- Adjustable: The height of the bracket is adjusted manually.
The projector can be suspended at a freely chosen position anywhere on the projector pillar.
- Stroke: 450 mm
- Guarantee: 5 years.
- Maximum load for projector rail: 8 kg
- Maximum total load: 40 kg
- Maximum board height: 1500 mm
- Minimum board height: 1170 mm
- Maximum board depth: 90 mm

NOTE: The maximum load specified refers to the weight that the bracket as a whole can support. This is the combined weight of the projector and interactive board. Using a lighter projector will allow a correspondingly heavier board to be used. For example, the board may weigh 36 kg if a projector weighing 4 kg is used. The experience of the user may vary, depending on the choice of projector and interactive board. This is not a factor within SMS' control.

Other information: The bracket is easy to move up and down, and the user can approach the board very closely since the bracket does not have a foot. This is advantageous for both children and people with disabilities. The SMS universal fitting can be used with nearly all interactive boards on the market.

See our Compatibility Guide to find out easily which interactive boards and projectors can be used with the Short Throw Wall Manual (together with the SMS Short Throw Unislide and the SMS Projector Pillar).

ART. NO.
AE025005**DESCRIPTION**

SMS Projector Short Throw Wall Manual A/White

NOTE: The projector pillar and the projector slide must be ordered separately. Article numbers for these are given below. Select the length that is suitable for your projector.

Choose one of the following alternatives:

A Choose the SMS projector pillar and projector slide.

B If the projector is sold with its own projector arm, choose an SMS adapter instead. See below for details.

A: Projector pillar


FS000450AW-P2	SMS Projector Short Throw 450 A/White
FS000680AW-P2	SMS Projector Short Throw 680 A/White
FS001202AW-P2	SMS Projector Short Throw 1200 A/White
FS001450AW-P2	SMS Projector Short Throw 1450 A/White

A: Projector slide

AE022021 SMS Projector ShortThrow UniSlide White

B: Adapter for projectors sold with an accompanying projector arm

AE019053	SMS Short Throw NEC Adapter Wall
AE023040	SMS Short Throw Smart Adapter
AE023041	SMS Short Throw Epson Adapter
AE023042	SMS Short Throw Hitachi Adapter



White plastic fittings give an elegant impression in any surroundings.

